

Builder's Choice Industrial Updraft Ceiling Fan Series 120 Volts, 0.68 amps, 60 hz.

Fan Body

Powder coated .0035" thick steel body housing.

Motor

1-speed, 1/4 HP, 1 phase, totally enclosed ball bearing, permanently lubricated, permanent split capacitor. 120 volt, 60 hz, 0.68 amp, 81 watt.

Unit Mounting

Downrod. All mounting hardware including a 16" downrod is included in box.

Finish


All white body.

Paddles

3 white powder coated steel paddles.

Shipping Information

UPC: 0-8316237190-4 Shipping Weight: 17.3 lbs.



9856UF

Updraft ceiling fan designed for use in agricultural settings including chicken houses, stables, and other areas where air needs to be circulated from the top of the building.

PROJECT	Ī						ARCHITECT			
LOCATIO	N						ENGINEER			
CONTRACTOR							SUBMITTED BY		DATE	
FAN NUMBER	MODEL NUMBER	CFM	IN W.C.	RPM	WATTS	AMPS	SONES	QTY		EQUIPMENT Marks



U.S.: 820 Lincoln Drive West Chester, Pennsylvania 19380-4466 Tel: (610) 692-7400 • 877-304-3785

Fax: (610) 696-8048